loblicht GmbH - Zum Möhnewehr 9 - D-59755 Arnsberg-Neheim - info@loblicht.de - Telefon +49 (0) 2932-9784-0

300101

Toni 3006 U 8400 840 O SX DA

- light strip, universal
- linear
- aluminium





Tender

light strip, universal, linear, Luminaire body aluminium, Silver anodized (E6/EV1), anodizing, visible screws, direct beam distribution, covering opal, 4000 K, CRI 80, Rated Luminous Flux 8400 lm, Rated power 52 W, Luminous Efficiency 162 lm/W, Mac Adams 3, UGR < 28, Luminance ≥65° 8618 cd/m², average rated life L 80 B10 70.000 h (for ambient temperature 25°C), switchable with integrated electrical control gear, electrical connection via 3 + 2-pole connection terminal up to 2.5mm², Mains voltage 230 V Net type 50/60 Hz, Glow wire strength 650°C, Protection class I, IP 40, Luminaire length 3006 mm, Luminaire width 45 mm, Height 74 mm, 4,3 kg.

Protection class	I
IP rating	IP 40

CE

Specifications

Rated Luminous Flux Φ_v:	8400 lm
Rated power P:	52 W
Color temperature T_{cp}:	4000 K
Luminance ≥ 65°:	8618 cd/m²
Average rated lifetime (Lx):	L 80 B10 70.000 h
Color rendering index CRI:	≥ 80
Luminous Efficiency η_v:	162 lm/W
UGR:	< 28

Dimensions & weight

Luminaire length:	3006 mm
Luminaire width:	45 mm
Height:	74 mm
Weight:	4,3 kg

Operating technology

Ambient temperature (ta):	25 °C
Mains voltage:	230 V
Net type (Hz):	50/60

Note

Required mounting accessories for Toni continuous-row lighting see: Downloads -> Installation instructions

All technical data, weights and dimensions have been carefully compiled. Errors excepted. Product illustrations are examples and may differ from the original. We reserve the right to make changes in the interests of progress.